

Amendments to the Abstract

Replace the abstract with the following replacement abstract:

~~The invention relates to a~~ A bicompartement bag ~~comprising~~
adapted to prepare a liquid solution has an assembly of two ~~strong~~
flexible outer sheets (1, 2), ~~through one of which sheets the~~ with
an access bushing (4) is affixed[[,]] through one of the sheets.
~~wherein the~~ The interior of ~~such~~ the bag is divided into two
chambers by ~~means of~~ a third separating flexible sheet (7) ~~provided~~
~~with~~ having a screen-like stripe (9) with its distal end located at
the bottom of the bag[[;]]. ~~said~~ The third separating sheet (7)
~~which, correspondingly with said bushing (4) is provided with~~ has a
bore (8) affixed around its edge onto the annular plane (10) of the
bushing end projecting into the bag[[;]]. ~~of said two chambers, a~~
The first chamber ~~is in communication~~ communicates with, by means
of through the bushing, ~~with it's related~~ a solvent inlet and it
is partially filled with ~~the~~ powdered solute[[,]]. ~~whereas the~~ The
inside of the second chamber ~~is provided inside with~~ has a layer
(5) separate from the bag[[,]]. The second chamber layer, selected
~~among~~ constructed of a woven or injected material ~~or the like,~~
~~freely extending~~ extends from a semicircular recess (6) made in
correspondence with ~~said~~ the bushing (4) to the bottom of the
second chamber. ~~and wherein said~~ The bushing provides the ~~necessary~~
~~means~~ opening for ~~the exit~~ removal of the resulting solution ~~thus~~

U.S. Appln. No.: 10/542,144
Atty. Docket No.: P70596US0

achieved. ~~The invention also relates to a process for
manufacturing a bag according to the invention.~~

For the examiner's convenience, a clean text version of the replacement abstract (150 words) is presented below:

A bicompartiment bag adapted to prepare a liquid solution has an assembly of two flexible outer sheets with an access bushing affixed through one of the sheets. The interior of the bag is divided into two chambers by a third flexible sheet having a screen-like stripe with its distal end located at the bottom of the bag. The third sheet has a bore affixed around its edge onto the annular plane of the bushing end projecting into the bag. The first chamber communicates with, through the bushing, a solvent inlet and is partially filled with powdered solute. The inside of the second chamber has a layer separate from the bag. The second chamber layer, constructed of a woven or injected material, extends from a semicircular recess made in correspondence with the bushing to the bottom of the second chamber. The bushing provides the opening for removal of the resulting solution.